
ECOUSTIC® SOFFIT ABSORBER





ECOUSTIC® SOFFIT ABSORBER .98" COLOR




^{*}The following colors for .98" Soffit Absorbers are supplied with a white core: Cameo, Cream, Dove, Fresco, Lunar, Mica, Natural, Oatmeal, Opal, Oyster, Sky, Spray, + White. All other colors in this thickness are supplied with a black core.



ECOUSTIC® SOFFIT ABSORBER 1.97" COLOR









ECOUSTIC® SOFFIT ABSORBER COLOR

Front View



Side View



COMPOSITION 100% PET (up to 65% recycled PET)

DIMENSIONS 47.25" x 47.25" or 23.6" x 47.25" +/- 1.5% (1200 x 1200mm or 600 x 1200mm) Custom sizes available, minimums

apply

FIRE RATING

ASTM E84 Class C AS/ISO 9705 BCA Group 1

APPLICATION Ceiling (adhesive + fastening required)

Please see the Installation & Care document on unikavaev.com for detailed information on mechanical

fastening.

ACOUSTIC

0.98" NRC 0.80 1.97" NRC 0.90

*Refer to graph on following page

THERMAL 0.98": R1.36 **RESISTANCE** 1.97": R0.68

LIGHTFASTNESS

ISO 105-B02 >6

How To Specify		
Product	Ecoustic® Soffit Absorber	
Thickness	0.98" or 1.97"	
Size	47.25" x 47.25" or 23.6" x 47.25"	
Color	Choose from 40 Ecoustic® Felt colors	

Designed for the Environment

- · California 01350 Emissions Compliant
- Recycled Content
- · Rapidly Renewable Content
- Low VOC
- · Greentag Level A Certified
- mindful MATERIALS
- Prop 65 Compliant
- Health Product Declaration®
- Environmental Product Declaration®
- Declare Compliant
- No FR Additives
- No Conflict Minerals
- · Red List Compliant


Building Rating Systems: Ecoustic® Soffit will contribute the following points for Green Star, LEED + WELL building standards

Criteria	Green Star	LEED	WELL
Recycled Content	√	√	N/A
Low VOC	√	√	
EPD	√	√	N/A
3 rd Party Greentag Level A Certification	√	~	√
Toxic Material Reduction	N/A	N/A	√
Sound Reducing Surfaces 0.98" + 1.97"	N/A	N/A	√



ECOUSTIC® SOFFIT ABSORBER ACOUSTIC

The sound-absorption has been tested in accordance with AS/ISO 354



Frequency	0.98"	1.97"
100	0.08	0.17
125	0.14	0.30
160	0.14	0.31
200	0.22	0.45
250	0.30	0.57
315	0.46	0.72
400	0.60	0.82
500	0.70	0.94
630	0.84	0.98
800	0.94	1.09
1000	1.02	1.11
1250	1.04	1.13
1600	1.07	1.11
2000	1.07	1.10
2500	1.07	1.05
3150	1.04	1.01
4000	0.99	0.99
5000	0.96	1.03
NRC	0.80	0.90



Ecoustic® Soffit Absorbers [QTY PER BOX]

0.98" Soffit: 47.25" x 47.25" [12] or 23.6" x 47.25" [24] 1.97" Soffit: 47.25" x 47.25" [6] or 23.6" x 47.25" [12]

- One color per box, box sets may not be mixed
- All dimensions are nominal with approx +/- 1.5%

IMPORTANT

Soffit Specification: Ecoustic® Soffit Absorber is an effective sound absorbing lining specifically designed to be directly fixed to soffits and ceilings where broadband sound absorption, absorbing low, medium and high frequencies, is required to control reverberant noise in rooms.

Structural Safety: We recommend all overhead product installations must comply with structural engineer's specifications. Soffit liner must be installed via mechanical fastening in addition to adhesive.

Moisture Absorption: Exposure to an atmosphere of 50% and 95% RH for four days provides moisture absorption of less than 0.2% per volume. As Ecoustic® Soffit Absorber is 100% polyester, it will not degrade over time due to moisture, mildew or rot in office environments.

Toxicity: Polyester is non-toxic and is classed the same as wood under the State of New York Article 15 Part 1120. Ecoustic® Soffit Absorbers do not contain any Red List Chemicals (USA EPA).

